4790 Old Frankstown Road • Monroeville, PA 15146-2096 Phone: (724) 325-3900 Fax: (724) 325-2340 www.cyphercompany.com rjm@cyphercompany.com BRANCH WAREHOUSE 290 South Highway 55 • Price, UT 84501-3532 Phone: (435) 613-0577 Fax: (435) 613-0575

## KEYSTONE™ AQUA-PETRO COMPOSITE HOSE

## KEYSTONE™ AOUA-PETRO

This composite hose replaces the bulky rubber suction and discharge hoses frequently used in the pump rental market. This durable suction and discharge hose provides excellent flexibility, light-weight handling and long service life. Keystone™ Aqua-Petro hose is suitable for water, oil and some chemicals used in fracking.

- AFTER ASSEMBLY ALL HOSES ARE PRESSURE TESTED AND CHECKED FOR CONDUCTIVITY
- TEST PRESSURE 4", 6", & 8" 375 PSI 10" & 12" 300 PSI
- GALVANIZED STEEL CAGE CRATES ARE ONLY SUITABLE FOR 4", 6" & 8" ID
  PRICE IS NOT INCLUDED WITH HOSE, MUST BE ORDERED SEPERATELY.
- 10" & 12" ID HOSES ARE FURNISHED WITH 2 LIFTING SLINGS FOR 10 FT.
  LENGTHS & 4 SLINGS FOR 20 FT LENGTHS (INCLUDED IN ASSY PRICE)
- ALL HOSE ASSEMBLIES HAVE A METAL CERTIFICATION TAG PERMANENTLY ATTACHED TO HOSE FITTING WITH SPECIFICATIONS AND SERIAL NO.
- BEND RADIUS TO CENTER LINE OF THE HOSE
- STANDARD LENGTHS 10FT & 20FT COUPLED FIXED x FLOATING CS 150 LB RF.
  FLANGES SWAGED EACH END.
- OTHER FITTING TYPES AVAILABLE BY SPECIAL ORDER
- HOSE ASSEMBLY PICTURED IS 8" ID X 20FT
- TEMPERATURE RATING -22 F TO 176 F
- HOSE BRANDED CONTINIOUS: LOGO, KEYSTONE™, ID, AQUA-PETRO, PSI WP

HOSE ID (INCHES)	4"	<mark>6"</mark>	<mark>8"</mark>	10"	12"
HOSE OD (OUTSIDE DIAMETER)	4.6"	6.9"	8.8"	10.9"	13.1"
MAX WP PSI	250	250	250	200	200
MIN BURST PRESSURE PSI	1000	1000	1000	800	800
BEND RADIUS TO HOSE CENTER LINE	15.7"	23.6"	31.5"	39.4"	47.0"
WEIGHT LB PER FOOT	4.0	7.4	10.1	15.1	18.5
150 # FLANGE & COUPLING FIXED END (LBS)	16.5	37.4	68.2	38.6	60.6
150 # FLANGE & COUPLING FLOATING END (LBS)	19.8	41.8	79.2	43.2	67.2
WEIGHT FOR 10 FT HOSE ASSY.	77.0	154.0	248.6	308.4	422.4
WEIGHT FOR 20 FT HOSE ASSY.	116.6	226.6	347.6	458.3	606.3





