Wyamada

Global Series

Air-Powered Double Diaphragm Pumps



G25AN

37 GPM Maximum Flow Rate
1 inch Port Size

The genesis of a new era is upon us! Specializing in pneumatically driven equipment for decades, we have combined genius technology with next generation manufacturing, enabling us to produce the latest genre of high quality pumps. The Global Series is now globally available for general industrial market applications.

Applications:























Technical Specifications

Maximum Flow Rate	37 GPM
PortSize	1" Female NPT
Air Supply Pressure	30-100 PSI
Liquid Temperature	32-180°F
Maximum Air Consumption	30 SCFM
Weight	17.4 lbs.
Maximum Size Solid	1/8"
NPT Dimensions	8.25"Lx8.5"Wx12.4"H
Air Inlet	3/8 " Female NPT
Body Material	Aluminum (ADC-12)
Discharge Volume Per Cycle	0.158 Gallons

W Yamada

THE CYPHER COMPANY 4790 Old Frankstown Road

Monroeville, PA 15146-2096 Phone: (724) 325-3900 Fax: (724) 325-2340 www.cyphercompany.com rjm@cyphercompany.com

obal Series

Air-Powered Double Diaphragm Pumps

G25AN



Toll Free: (855) 336-5425 www.gseriespump.com

Kynar[®] is a registered trademark of Arkema. NordelTM is a trademark of DuPont Dow Elastomers.

Viton[®] is a registered trademark of DuPont Performance Elastomers.

Features & Benefits

- Truly non-lubricated (no grease pre-pack) / maintenance free air distribution system
- Stall Free / Ice Free operation
- Fewer Wearing Parts
- Ease of Repair Quick teardown / Rebuild
- 20% less air consumption over competitor's pumps
- Drop in replacement for other brands

Graphite filled Ekonol® seal rings (lube free)





non-lubricated piloting system



Elastomeric Options

- Neoprene[™]
- Santoprene®
- EPDM (Nordel)
- Hytrel®

Local Distributor:

Form# GS0417